AL SAFE 205

ENVIROCHEM

425 Whitehead Avenue South River, NJ 08882 Phone—732-238-6700 Fax—732-238-5590

GENERAL DESCRIPTION: AL-SAFE 205 is a granular, machine warewashing compound that is soft metal safe and designed to handle moderate soil loads in soft to medium-hard water at normal warewashing concentrations.

AL-SAFE 205 is not only packed with strong cleaning and destaining agents, but also the glaze and metal protectants necessary to assure a safe and effective wash.

AL-SAFE 205 will deliver sparkling ware with one pass through the dishmachine when used in conjunction with RINSE ALL or HEAVY DUTY RINSE ALL.

AL-SAFE 205 solutions are safe to use on china, plastics, glassware, aluminum, pewter, and silver. They will not attack machine parts thereby reducing parts replacement and chance of breakdown. In addition, AL-SAFE 205 conditions hard water and prevents formation of scale on machines.

PHYSICAL PROPERTIES:

3 Grains Per Gallon at 0.1%

RECOMMENDED RANGE OF USE CONCENTRATIONS:

Titrate with Institutional Test Kit. Use range is 0.15% to 0.3%, or 6 to 12 drops (each drop = .025%) using a 10 ml sample and 3 drops of Brom Phenol Blue Indicator Solution. Select actual use concentration to handle water hardness and soil load.

NOTE: To properly titrate, adjust for raw water alkalinity by titrating H_2O just as you would a detergent solution. Subtract that number from total drop titration to derive intended detergent concentration. Example: Raw water titrates 1 drop, total drop titration equals 11 drops. $(11 - 1 = 10 \times .025\% = 0.25\%)$

HANDLING PRECAUTIONS:

CAUTION: WARNING KEEP OUT OF REACH OF CHILDREN.

Alkaline powder. Contact with skin and eyes may cause irritation. Harmful if swallowed. Flood with water if splashed in eyes. Flush with water for 15 minutes and consult physician immediately. If ingested, drink large amounts of milk, milk of magnesia or gelatin, or if these are not available, drink large amounts of water. DO NOT induce vomitiing. Obtain prompt medical attention.

PACKAGING:

30 - 2 lb. case - 60 lbs net / 63 lbs gross 50 lb box - 50 lbs net / 53 lbs gross

Seller makes no warranty, expressed or implied, concerning the use of this product other than indicated on the label. Buyer assumes all risk of use and/or handling of this material when such use and/or handling is contrary to label instructions.