

# Rinse All High Solid

ENVIROCHEM

425 Whitehead Avenue  
South River, NJ 08882  
Phone—732-238-6700  
Fax—732-238-5590

**GENERAL DESCRIPTION:** RINSE ALL HIGH SOLID is a unique blend of specialized surfactants. RINSE ALL HIGH SOLID is formulated specifically to attain spotless, cloudless results in areas where high dissolved solids are a problem. The excellent sheeting action of RINSE ALL HIGH SOLID helps eliminate hard and alkaline water film deposits from flatware, glasses and dishware. It does this by allowing rinse water to drain quickly, before the dissolved solids in the water have an opportunity to precipitate onto the ware.

## PROPERTIES:

Chemical composition . . . Organic, nonionic wetting agents, concentrate stabilizers  
pH , 4% ..... 2.8  
Specific Gravity ..... 1.02(8.56 pounds per gallon)  
Foam ..... Acts as a mild suppressant  
Wetting Ability ..... Instant, complete  
Odor ..... Not residual

## INSTRUCTIONS FOR USE:

RINSE ALL HIGH SOLID is designed specifically to solve the clouding of glassware caused by the amount of dissolved solids in the water. RINSE ALL HIGH SOLID is recommended for use at a concentration between a minimum of 150 ppm (1:6,500) and a maximum of 450 ppm (1:2,200). The actual use concentration is determined by the individual operating conditions. For control of dissolved solids in excess of 900 ppm, it is advisable to maintain a minimum concentration of 450 ppm (1:2,200). Where the dissolved solids are 300 ppm or less, RINSE ALL HIGH SOLIDS may be used at concentrations as low as 150 ppm (1:6,500). For optimum results, install the rinse injection fitting as far back in the line from the rinse jets as possible. This allows thorough mixing of RINSE ALL HIGH SOLID with the water supply before it emerges from the final rinse jets.

Final rinse temperature should be maintained as close to the 1800 F (820 C) minimum as possible and should not exceed 1900 F (870 C) in any case. Check the final rinse pressure and set at manufacturer's recommended level. Also, inspect final rinse for spray atomization. Adjust the rinse injector to feed RINSE ALL HIGH SOLID at the required concentration to achieve the rapid sheeting of water from the ware.

## HANDLING PRECAUTIONS:

### CAUTION - FIRST AID

**EYES:** Flush with water for at least 15 minutes. If irritation persists, obtain medical attention. **SKIN:** Wash with plenty of water for 15 minutes. If irritation occurs and persists, obtain medical attention. **INHALATION:** Remove from exposure. If discomfort occurs and persists, obtain medical attention. **INGESTION:** Drink water to dilute. Obtain medical advice by phone. **DECONTAMINATION PROCEDURE:** Wash with soap and water.

### KEEP OUT OF REACH OF CHILDREN

## PACKAGING:

4 /1 gal plastic bottles - 39 lbs. net/42 lbs. gross  
5 gal plastic pail - 48 lbs. net/51 lbs. gross

Seller makes no warranty, expressed or implied, concerning the use of this product other than indicated on the label. Buyer assumes all risk of use and/or handling of this material when such use and/or handling is contrary to label instructions.