

# TWILIGHT SPRAY BUFF

ENVIROCHEM

425 Whitehead Avenue  
South River, NJ 08882  
Phone—732-238-6700  
Fax— 732-238-5590

**TWILIGHT** is a unique all acrylic floor finish designed to meet the demands for in between regular floor maintenance to preserve that wet look finish. **TWILIGHT** can be used on all floors previously protected with *Supreme Shine* or *Econoshine*. **TWILIGHT** removes dirt, scuffs and black heel marks and restores your floor to its previous beauty. Floors can be burnished with standard, high or ultra high speed equipment and pads.

## PROPERTIES

Solids . . . . .	<10%
Slip Resistance, COF. . . . .	>0.50
Recoatibility, ASTM D315. . . . .	Exceeds
Detergent Resistance, ASTM D179. . . . .	Exceeds
pH. . . . .	8.0-8.5
Dry/Recoat Time. . . . .	30 min.
Freeze/Thaw, ASTM D3209. . . . .	Passes
Soil Resistance, ASTM D3206 . . . . .	Excellent
Coverage. . . . .	Up to 3000 sq. ft per gal.

## DIRECTIONS FOR USE

Use on the floor only if previous protected with Distributor's Choice Econoshine or Distributor's Ultra Supreme Shine.

1. Set up wet floor signs to avoid costly slip fall occasions.
2. Follow all label instructions and precautions on all chemicals.
3. Remove loose soils by sweeping . If floor is heavily soiled, damp mop first.
4. Before spray buffing the floor, surface should be clean and dry.
5. Apply **TWILIGHT** to a small area using a trigger sprayer or other suitable dispensing device.
6. Do not allow finish to dry on floor; sread evenly with a low speed buffing machine equipped with a red pad.
7. return on a second and third pass to clean and remove scuffs and renew shine to its original brilliance.